

Sub
a1

203220-02998001

BRIAN C. KUNZLER
ATTORNEY AT LAW
10 WEST 100 SOUTH, SUITE 425
SALT LAKE CITY, UTAH 84101

1. A method for recursive ray casting, the method comprising:
providing a ray bundle of a selected position, direction and size;
conducting a proximity test of a selected proximity at the selected position; and
advancing the ray bundle a first casting distance when the proximity test is
negative.
2. The method of claim 1, wherein the first casting distance corresponds to the
selected proximity.
3. The method of claim 1, wherein the size of the ray bundle corresponds to the
selected proximity.
4. The method of claim 1, further comprising advancing a second casting distance
when the proximity test is positive.
5. The method of claim 1, further comprising retreating a second casting distance
when the proximity test is positive.
6. The method of claim 1, further comprising subdividing the ray bundle into child
bundles when the proximity test is positive.
7. The method of claim 6, further comprising traversing and subdividing until each
child bundle is a single ray.

2022-02998001

BRIAN C. KUNZLER
ATTORNEY AT LAW
10 WEST 100 SOUTH, SUITE 425
SALT LAKE CITY, UTAH 84101

1 8. The method of claim 6, wherein subdividing comprises partitioning along the
2 largest ray bundle dimension.

3
4 9. The method of claim 6, wherein subdividing comprises partitioning along each
5 ray bundle dimension.

6
7 10. The method of claim 6, further comprising combining child bundles of a
8 subdivided ray bundle when the proximity test of the ray bundle is negative.

9
10
11 11. The method of claim 1, wherein the proximity test comprises testing boolean
12 flags.

13
14 12. The method of claim 1, wherein the proximity test comprises accessing a distance
15 grid.

16
17
18 13. The method of claim 1, wherein the proximity test comprises accessing a list of
19 proximate objects.

14. A method for recursive ray casting, the method comprising:
- providing a ray bundle of a selected position, direction and size;
- conducting a proximity test of a selected proximity at the selected position;
- advancing the ray bundle a first casting distance when the proximity test is negative, the first casting distance and the size of the ray bundle corresponding to the selected proximity;
- retreating a second casting distance and subdividing the ray bundle into child bundles when the proximity test is positive; and
- advancing, subdividing and retreating until each child bundle is a single ray.
15. An apparatus for recursive ray casting, the apparatus comprising:
- a proximity tester configured to receive a bundle position and provide a first hit signal indicating whether the bundle position is proximate to a graphical object; and
- a bundle caster configured to advance the bundle position.
16. The apparatus of claim 15, further comprising an occlusion detector operably connected to the bundle caster, the occlusion detector configured to receive a pixel set descriptor and a minimum z-depth, and to provide a mask indicating which pixels within the pixel set are known to be occluded.
17. The apparatus of claim 16, wherein the pixel set is defined by an area selected from a scanline span, a rectangle, and a triangle.

203220-0299007

BRIAN C. KUNZLER
ATTORNEY AT LAW
10 WEST 100 SOUTH, SUITE 425
SALT LAKE CITY, UTAH 84101

1 18. The apparatus of claim 16, wherein the occlusion detector is configured to operate
2 at a lower depth resolution than the bundle caster.

3
4 19. The apparatus of claim 15, wherein the bundle caster comprises at least one
5 register file, each register file thereof coupled to an ALU.
6

7
8 20. The apparatus of claim 15, further comprising a collision tester configured to
9 receive a ray position and provide a second hit signal indicating whether the ray position
10 is on or within the graphical object.
11

12 21. The apparatus of claim 20, further comprising a ray caster configured to advance
13 the ray position.
14

15
16 22. The apparatus of claim 21, wherein the ray caster comprises at least one register
17 file, each register file thereof coupled to an ALU.
18

19 23. The apparatus of claim 22, wherein the ray caster is operably connected to the
20 occlusion detector.
21
22
23
24
25
26
27

